

# D2P Pro Horizontal Single-axis Tracker



## Advantages

- Multi-drive System for Maximum Aeroelastic Stability
- Advanced Smart Control
- Flexible Layout for Irregular Terrains

Power Generation Increased

**Up to 30%**

Newest Generation 2 x Portrait Smart Solar Tracking System

## Features

The innovative model is characterized by its high system stability throughout the life of the solution, maximizing the energy output for solar plants. This system can be flexibly used for sites with challenging soils and delivers a perfect solution for Agrivoltaics and Fisheryvoltaics projects.

- Higher power density - supports up to 120 modules with 4x1,500V-strings
- Lower construction costs - requires 135 posts per MW
- Bifacial compatibility - secures the maximum power generation potentially up to 30% more



IEC 62817



Wind Tunnel Test

## Technical Details

PV-Modules	
PV-Modules supported	Compatible with modules up to 600W or 210 cells
Structure	
Type	Horizontal single-axis, independent row
Maximum capacity per row	65kWp (Estimated with 545W PV-Modules)
PV-Modules quantity per row	Up to 120 modules, depending on module string length
Bifacial features	Available with optimized central torque tube gap
PV-Modules configuration	2 in portrait 4 x 1,500 strings per standard tracker
PV-Modules attachment	Self-grounding and electrical tool-actuated
Tracking range	±60°(120°)
Tracking accuracy	≤2°
Ground coverage ratio (GCR)	30% to 50%
Structural materials	HDG steel
Foundation	Steel pile, PHC pile, Concrete foundation
Quantity of foundation/ MW	Normally about 135 PCS/MW (Standard W8 section foundation posts)
Electrical	
Motor type	24V DC Motor
Drive method	Patented multi-drive
Solar tracking method	Astronomical algorithm + closed-loop control integrated AI control tracking algorithm
Signal transmission	Wire (RS485) or wireless (Zigbee)
Backtracking	Yes
Power supply	Option1: Array powered, integrated backup battery Option2: AC powered, customer-provided AC circuit
Protection Function	
Night stow mode	Yes
Wind protection	Intelligent wind stowing with self-locking Multi-drive system for maximum array stability in all wind conditions
Environment	
Wind load	Up to 40m/s
Operating temperature	Array powered: -20°C to +60°C AC powered: -30°C to +60°C
Civil and Installation	
Slope tolerance	North-south up to 20%, East-west with no limits
Special tools	Not required
Other	
IP rating	IP65
Onsite training & commissioning	Yes
Codes and standards	UL 3703   UL 2703   IEC 62817
Warranty	10 years for main structure 5 years for drive and control components



TUV Certification



RWDI Wind Tunnel Test

### Clenergy

1001-1009 Min'an Rd,  
Huoju Hi-tech Ind. Dev. Zone Xiang'an  
District 361101, Xiamen, Fujian, China


Phone: +86 592 311 0088

Email: sales@clenergy.com

Web: www.clenergy.com

 Clenergy AUS & NZ

 @Clenergy

 @Clenergy\_global

 @Clenergy

 @ClenergyClub